

Rocky Mountain Interagncy Engine Academy 2013

ROCKY MOUNTAIN ENGINE ACADEMY 2013 PRE-TEST #1

Name	Agency/Home Unit
	Final Score: / 133
	1 mai 5corc 155
Questions 1-20- Pick the correct answer (A,B,C, D) for the valve names and functions for the

1. Valve #1: (2 pts)

following numbers:

- A. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines.
- B. OVERBOARD SUCTION Flows water from an external source to pump.
- C. TANK TO PUMP Flows water from the tank to the pump.
- D. PUMP TO TANK Flows water from the pump to the tank.
- 2. Valve #2: (2 pts)
 - A. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines.
 - B. OVERBOARD SUCTION Flows water from an external source to pump.
 - C. TANK TO PUMP Flows water from the tank to the pump.
 - D. PUMP TO TANK Flows water from the pump to the tank.
- 3. Valve #3: (2 pts)
 - A. OVERBOARD SUCTION Flows water from an external source to pump.
 - B. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines.
 - C. PRIMER With the priming unit, allows the centrifugal pump to be primed.
 - D. GRAVITY TANK DRAIN Drains water tank
- 4. Valve #4: (2 pts)
 - A. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines.
 - B. PRIMER With the priming unit, allows the centrifugal pump to be primed.
 - C. GRAVITY TANK DRAIN Drains water tank
 - D. HOSE REEL Flows water from the pump to the hose reel(s).
- 5. Valve #5: (2 pts)
 - A. IN-TANK SHUT-OFF Shuts off water in the tank to the pump.
 - B. PRIMER With the priming unit, allows the centrifugal pump to be primed.
 - C. AUXILIARY DISCHARGE Flows water from the pump to an engine protection discharge.
 - D. BYPASS Circulates water from the pump back to the tank for pump cooling.
- 6. Valve #6: (2 pts)
 - A. IN-TANK SHUT-OFF Shuts off water in the tank to the pump.
 - B. PRIMER With the priming unit, allows the centrifugal pump to be primed.
 - C. AUXILIARY DISCHARGE Flows water from the pump to an engine protection discharge.
 - D. BYPASS Circulates water from the pump back to the tank for pump cooling.



7. Valve #7: (2 pts)

- A. WATER DISCHARGE 1.5" overboard discharge plumbed prior to the foam injection.
- B. ADJUSTABLE PRESSURE RELIEF Relieves excess pressure, preventing pump damage.
- C. IN-TANK SHUT-OFF Shuts off water in the tank to the pump.
- D. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling.
- 8. Valve #8: (2 pts)
 - A. FEEDER VALVE For clean water discharge and #2 valve.
 - B. PUMP & PLUMBING DRAIN Drains water from the pump and plumbing...
 - C. IN-TANK SHUT-OFF Shuts off water in the tank to the pump.
 - D. OVERBOARD SUCTION Flows water from an external source to pump.
- 9. Valve #9: (2 pts)
 - A. 40 GALLON RESERVE Flows reserve 40 gallons to the pump
 - B. GRAVITY TANK DRAIN Drains water tank.
 - C. LOW VOLUME GRAVITY Gravity discharge for backpack fill.
 - D. HOSE REEL Flows water from the pump to the hose reel(s).
- 10. Valve #10: (2 pts)
 - A. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
 - B. ENGINE COOLER Circulates cool water from engine
 - C. FEEDER VALVE For clean water discharge and #2 valve
 - D. IN-TANK SHUT-OFF Shuts off water in the tank to the pump.
- 11. Valve #11: (2 pts)
 - A. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
 - B. PUMP & PLUMBING DRAIN Drains water from the pump and plumbing.
 - C. ENGINE COOLER Circulates cool water from engine
 - D. PUMP COOLANT CLEAN-OUT Flushes debris from plumbing
- 12. Valve #12: (2 pts)
 - A. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
 - B. PUMP & PLUMBING DRAIN Drains water from the pump and plumbing.
 - C. ENGINE COOLER Circulates cool water from engine
 - D. PUMP COOLANT CLEAN-OUT Flushes debris from plumbing
- 13. Valve #13: (2 pts)
 - A. GRAVITY TANK DRAIN Drains water tank.
 - B. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
 - C. ENGINE COOLER Circulates cool water from engine.
 - D. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines

14. Valve #14: (2 pts)

- A. GRAVITY TANK DRAIN Drains water tank.
- B. FOAM BYPASS Water routed around foam unit (Clean water discharge).
- C. ENGINE COOLER Circulates cool water from engine.
- D. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines

15. Valve #15: (2 pts)

- A. PUMP TRANSFER Switches the pump to either parallel or series operation
- B. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
- C. ENGINE COOLER Circulates cool water from engine.
- D. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines

16. Valve #16: (2 pts)

- A. GRAVITY TANK DRAIN Drains water tank.
- B. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
- C. ENGINE COOLER Circulates cool water from engine.
- D. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines

17. Valve #17: (2 pts)

- A. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
- B. ENGINE COOLER Circulates cool water from engine.
- C. PRIMER With the priming unit, allows the centrifugal pump to be primed.
- D. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines

18. Valve #18: (2 pts)

- A. GRAVITY TANK DRAIN Drains water tank.
- B. IN-TANK SHUT-OFF Shuts off water in the tank to the pump
- C. ENGINE COOLER Circulates cool water from engine.
- D. LOW VOLUME GRAVITY Gravity discharge for backpack fill.

19. Valve #19: (2 pts)

- A. GRAVITY TANK DRAIN Drains water tank.
- B. CLEAN WATER DISCHARGE 1.5" overboard discharge plumbed prior to the foam injection.
- C. ENGINE COOLER Circulates cool water from engine.
- D. PUMP & PLUMBING DRAIN Drains water from the pump and plumbing.

20. Valve #20: (2 pts)

- A. FEEDER VALVE For clean water discharge and #2 valve
- B. PUMP BYPASS Circulates water from the pump back to the tank for pump cooling
- C. ENGINE COOLER Circulates cool water from engine.
- D. OVERBOARD DISCHARGE Flows water from the pump to the main discharge lines
- 21. To pump water through a 1-1/2" line from a pond to a fire, valves #3 and #8 must be opened. (1pt)
 - A. TRUE B. FALSE

22.	To keep a Model 52 engine with a full tank of water ready during freezing weather, which valve/valves should be closed? (1pt)						
		A.	#1, #2, #17				
		В.	#4				
		C.	#11				
		D.	#3, #8				
23.	How many in		vacuum are necessary t	to lift v	water six fee	t? (1pt)	
		A.	10 inches				
		В.	8 inches				
		C.	12 inches				
		D.	6 inches				
24.	A Model 52	engine	has a	per the	e 2003 Wate	r Handling Guide: (1pt)	
		A.	Single Stage Positive	Displa	acement Pum	p	
		B.	2 Stage Centrifugal Pu	ump		-	
		C.	4 Stage Centrifugal Po	ump			
		D.	3 Stage Positive Displ	laceme	ent Pump		
25.	A positive di	isplaceı	nent pump should have	a pres	sure relief va	alve. (1pt)	
		A.	TRUE	B.	FALSE		
26.	What do the	follow	ng abbreviations mean?	' (6 pt	es)		
		GVW	TR –				
		NPSI	H –				
		NH –					
		GPM					
		PSI –					
		CJRL	,-				
27.	When testing fire	re hose	the total length of each	line to	ested shall no	ot exceed: (1pt)	
		A.	300 ft.				
		B.	150 ft.				
		C.	100 ft.				
		D.	any length needed				

28. The pump on Model 7 Water Handling Guide		d at	gpm @	psi. per the 2003
29. How many gallons of	water are contained in a	100 ft.	section of 1-1/2" hose?	(1 pt)
A. B. C. D.	12 gal. 5 gal. 7 gal. 9 gal.			
30. One PSI lifts water	feet. (1 pt)			
31. Explain friction loss.	(1 pt)			
32. The friction loss in 1-	inch hose is approximate	ly 6 tii B.	mes greater than 1-1/2" l	nose. (1 pt)
33. Friction loss decreases	s as flow (GPM) increase	es. (1 ₁	pt)	
A.	TRUE	В.	FALSE	
34. A "Floto-Pump" is a s	self-priming pump and ca	ın be s	tarted before it is set in v	water. (1 pt)
A.	TRUE	B.	FALSE	
35. When drafting from a	stream, the suction scree	n shou	ald be deep enough to m	aintain a prime. (1 pt)
A.	TRUE	B.	FALSE	
36. Which of the following	ng conditions can cause ca	avitati	on in a fire pump? (1 pt)
A. B. C. D. E.	Rising water temperat A blocked or inadequa Using too small or too All of the above None of the above	ate suc	tion strainer	

	37. After off road use with an engine, it is advisable to check for rocks between the duals and for possible tire sidewall damage. (1 pt)				
		A.	TRUE	B.	FALSE
38	A backup per	rson is onl	y required when you c	annot se	ee behind the engine. (1 pt)
		A.	TRUE	B.	FALSE
39.]	Name the No	A. Life B. Pro	y in all fire services. (e/Safety perty Protection ources Protection	1 pt)	
40.	Diesel engine	es are just	naturally oily so leaks	are to b	e expected. (1 pt)
		A.	TRUE	B.	FALSE
41.	Pick the best A. Belt is B. Belt is C. Belt is D. None the	loose dirty cracked	what is a probable cau	se of a '	'howling, squealing'' fan belt. (1 pt)
42.	What kind of A. Oil B. Water C. Other		nation in the fuel system	n is the	"typical" cause of diesel engine failure? (1 pt)

- 43. What are four items to check during a pre-use inspection (pick the best answer): (2 pts)
 - A. Tires, Lights/signals, engine oil level, coolant level in radiator,
 - B. Windshield wipers, tires, map kit, equipment maintenance log, radio
 - C. Brakes, driver license, first aid kit, windows

- 44. Which one of below is <u>not</u> part of Leader's Intent (according to the IRPG) (1 pt)
 - A. End State
 - B. Task
 - C. Direction
 - D. Purpose
- 45. Which of the following is not part of Risk Management Process (according to the IRPG) (1 pt)
 - A. Evaluate
 - B. Hazard Control
 - C. Decision Point
 - D. Hazard Assessment
 - E. Situation Awareness
 - F. Hazard Avoidance


Hydraulic Calculations notes:

Your work must be legible and your answers must be +/- 5psi of the correct answer to receive credit.


There are <u>major variations</u> between different manufactures of friction loss calculators and differences between printings of the same calculators. If your answer is +/-5psi and you have checked your work to identify the variance it may be no more than the calculator you're using. Ask your instructor in class if you have concerns.

Bring your workbook, friction loss calculator, regular calculator, and sample problems to the Academy.


46.



47.




48.



Solution #50 (5 pts.)

NP= H= FL GPM FL 1" = <u>FL 1½"=</u> PDP=

49.



Solution #51 (4 pts.)

FL

GPM

NP= H=


l=

FL 1½"=

PDP=




50.




Solution #52 (5 pts.)

NP= H= FL GPM FL 1"= <u>FL 1½"=</u> PDP=


51.





52.



53.










55.



Solution #55b @1/4" tip (4 pts.) NP= H= FL GPM FL 1" = FL 1½" = FL 1½" = FL 1½" = FL 1½" =

PDP=